

Features:

- 3½ Digits
- 4000 Counts
- True RMS
- NCV & Line

DC VOLTAGE

Range	Resolution	Accuracy
400mV	0.1mV	±(0.5% +3) Impedance Approx 10MΩ
4V	0.001V	
40V	0.01V	
400V	0.1V	
600V	1V	

AC VOLTAGE

Range	Resolution	Accuracy
4V	0.001V	±(0.8% +3) Impedance Approx 10MΩ Frequency Response 40Hz+1KHz:TRMS
40V	0.01V	
400V	0.1V	
600V	1V	

Continuity

<Approx 50Ω Buzzer will sound and the indicator light will be on

RESISTANCE

Range	Resolution	Accuracy
400Ω	0.1Ω	±(1.0% +5)
4kΩ	0.001kΩ	
40kΩ	0.01kΩ	
400kΩ	0.1kΩ	
4MΩ	0.001MΩ	
40MΩ	0.01MΩ	

FREQUENCY

Range	Resolution	Accuracy
4Hz	0.001Hz	±(1.0% +5)
40Hz	0.01Hz	
400Hz	0.1Hz	
4KHz	0.00KHz	
40KHz	0.01KHz	
400KHz	0.1KHz	
4MHz	0.001MHz	

Overload Protection : 250V

- Standard Accessories : Test Lead, Manual, Carry Case
- Dimension : 127(H) x 66(W) x19 (D)mm

11S



Features:

- 3¾ Digit
- 6,000 Count
- Color Display
- True RMS
- Input Jack Indication
- Fuse Burn Indication

DC VOLTAGE

Range	Resolution	Accuracy
600mV	0.1mV	±0.5% + 3 Impedance Approx.10MΩ
6V	0.001V	
60V	0.01V	
600V	1V	

A/C DC CURRENT

Range	Resolution	Accuracy
600mA	0.1mA	±1.2% of rdg + 3 digits
6A	0.001A	
10A	0.01A	

Overload Protection : F10A/250V fuse
Frequency Response: 40Hz~1kHz; TRMS

Capacitance

Range	Resolution	Accuracy
6nF	0.001nF	±4.0% of rdg + 2 digits
60nF	0.01nF	
600nF	0.1nF	
6μF	0.0001μF	
60μF	0.01μF	
600μF	0.1μF	±5.0% of rdg + 5 digits
6mF	0.001mF	
60mF	0.01mF	

Overload Protection : 250V

AC VOLTAGE

Range	Resolution	Accuracy
6V	0.001V	±0.8% of rdg + 3 digits
60	0.01V	
600V	1V	

Impedance : Approx. 10M
Frequency Response : 40Hz~1kHz, TRMS

RESISTANCE

Range	Resolution	Accuracy
600Ω	0.1Ω	±1.0% of rdg + 5 digits
6kΩ	0.001KΩ	
60kΩ	0.01KΩ	
600kΩ	0.1KΩ	
6MΩ	0.001MΩ	
60MΩ	0.01MΩ	

FREQUENCY/DUTY

Range	Resolution	Accuracy
6Hz	0.001Hz	±1.0% of rdg + 3 digits
60Hz	0.01Hz	
600Hz	0.1Hz	
6KHz	0.001KHz	
60KHz	0.01KHz	
600KHz	0.1KHz	
6MHz	0.001MHz	
10MHz	0.01MHz	±1.0% of rdg + 3 digits
1.0~99.0%	0.1%	

Diode/Continuity

- Display diode voltage drop
-) Approx. 50, Buzzer will sound and the indicator light will be on

Temperature

Range	Accuracy
'C'	-40°C~0°C ±3°C
	0°C~1000°C ±2.0% or ±2°C
'F'	-40°F~32°F ±6°F
	32°F~1832°F ±2.0% or ±4°C

Resolution : 1°C/1°F
Note : use K-type thermocouple probe

- Standard Accessories : Test Lead, Manual, Carry Case
- Dimension : 146(H) x 73(W) x 26(D)mm

15S

