

MECO-G[®]

SINCE 1982

DIGITAL TACHO METER CONTACT / NON-CONTACT TYPE MODEL: R-2241A

NEW**NEW!**Preliminary
Data

CE

**R-2241A**

Display	: 5 DIGIT, 18mm LCD Display
Measuring Range	: Non- Contact: 2.5 ~ 99,999 RPM/min Contact: 0.5 ~ 19999 RPM Surface Speed: 0.05 ~ 1999.9m/min / 99999m Surface Distance: 0.05 ~ 99999m
Resolution	: 0.1RPM (2.5~999.9RPM) / 1RPM (over 1000RPM) Contact: 0.1RPM (0.5~999.9RPM) / 1RPM (Over 1000RPM) Surface: 0.01m/min (0.05 ~ 99.99m/min) / 0.1m/min (over 100m/min) Surface Distance: 0.02m (0.05 ~ 99999m)
Accuracy	: ±(0.05% +1Digit)
Sampling Time	: 0.8 Sec. (Over 60RPM)
Test Range	: Auto
Memory	: Max. Value, min. value and last value will be stored.
Detecting Distance	: 50 To 500mm
Time Base	: 6MHz crystal oscillator
Circuit	: Exclusive one-chip of microcomputer LSI circuit
Battery	: 4x1.5V AA Battery
Power Consumption	: Approx. 40mA (while operating)
Op. Temperature	: 0~50°C (32~122°F)
Size	: 210x74x37mm
Weight	: Approx. 235g (including batteries)
Accessories	: User Manual, Carrying Case, 4 Batteries 2pcs of Reflecting strip (350mm)