

# **DIGITAL INSULATION TESTER**

# NEW

Preliminary Data

CE



Model: R-DT903A



Model: R-DT945K

#### Introduction:

"MECO-G" has introduced a multi-range 3½ Dgt. (1999 Counts) Digital Insulation Tester Model: R-DT903A and R-DT945K. It has 3 Voltage Ranges, 250V/500V/1000V and 1000V/2500V/5000V respectively.

R-DT903A has two MOhms (M $\Omega$ ) ranges, 0-200M $\Omega$  and 0-2000M $\Omega$  and R-DT945K is auto-ranging upto 20G $\Omega$ 

AC voltage measurement upto 750VAC is available. Voltage is maintained from 10% to 100% of the insulation resistance range.

## Special Functions:

- \* 3½ Digit (1999 Counts) Large Display with Back light
- \* High Accuracy ±(5% + 5dgts) for Insulation Measurement. and ±(1% + 6dgts) for VAC Measurement
- \* LCD Back Light Function with Indicator Switch.
- \* Measurement of AC voltage upto 750VAC.

#### **Electrical Specifications: R-DT903A**

Accuracy ± (% reading + digits) at 23°C ± 5°C; RH≤ 75%

- LED Indicator for HV (High Voltage)
- \* Inbuild Protection Circuit to prevent the harm of reverse voltages.
- Battery Operated / AC adapter (At additional cost)
- 3 Ranges of Insulation Measurement.

| Specification          | Test Voltage        | Range                             | Accuracy      | Resolution           |
|------------------------|---------------------|-----------------------------------|---------------|----------------------|
| Insulation Resistance  | 250V/500V/1000V     | 0-200M $\Omega$ to 2000M $\Omega$ | ±(5% + 5dgts) | $0.01 	ext{M}\Omega$ |
| AC Voltage Measurement | 0-750VAC (40-400Hz) | -                                 | ±(1% + 6dgts) | 1V                   |

### **Electrical Specifications: R-DT945K**

Accuracy ± (% reading + digits) at 23°C ± 5°C; RH≤ 75%

| Specification          | Test Voltage        | Range                                     | Accuracy      | Resolution |
|------------------------|---------------------|---|---------------|------------|
| Insulation Resistance  | 1000V/2500V/5000V   | 1M $\Omega$ -10G $\Omega$ to 20G $\Omega$ | ±(5% + 5dgts) | 0.1ΜΩ      |
| AC Voltage Measurement | 0-750VAC (40-400Hz) | -   | ±(1% + 6dgts) | 1V         |

### **General Specifications:**

| ocheral opcomedions.   |   |  |
|------------------------|---|--|
| Display                | 3½ Dgt. (1999 Counts) Large LCD Display with 33mm Display Height. |  |
| Accuracy               | ±(5% + 5dgs) for Insulation Measurement.                          |  |
|                        | ±(1% + 6dgts) for VAC Measurement                                 |  |
| Low Battery Indication | <u></u>   |  |
| Operating Temperature  | 0°C to 40°C (RH ≤ 85%)  |  |
| StorageTemperature     | -10°C to 50°C (RH ≤ 75%)  |  |
| Insulation Resistance  | $\geq 500 M\Omega / 1000 V$                                       |  |
| Voltage Withstand      | 2KV for 1 min.  |  |
| Dimensions             | 170 x 110 x 60mm  |  |
| Weight                 | Approx. 550gms including batteries                                |  |
| Power                  | 9V (6 x 1.5V) (R6AA size batteries) or AC Adaptor 9VDC            |  |
| Accessories            | 1. Insulation Test leads for High Voltage x 1                     |  |
|                        | 2. Batteries (R6AA size batteries) 1.5V x 6                       |  |
|                        | 3. Instruction Manual   |  |
|                        | 4. Carrying Case  |  |
|                        | 5. Shielding Line (Only with R-DT945K)                            |  |
|                        | 6. Adaptor (At additional Cost)                                   |  |