


**MODEL: METCAT** 

## DIGITAL UNIVERSAL TEMPERATURE CONTROLLER

**METRAVI** Universal temperature controller

is a Microcontroller based universal controller for J, K and RTD(Pt-100) sensors. Its user friendly setup features ensures easy setup and operation. The controller has a single set point which can be programmed for rising (heat) or reducing (cool) controlling setpoints.



The bright 3 1/2 digit RED seven segment display is easy to read from a distance.

The meter has a standard bezel size of 96mm x 96 mm with mounting clamps for easy installation.

## **DEFAULT VALUES:**

INPUT: J Cntr :On Hys : 01 : 20 Pb : 20 CVC Rly : Heat : 0600 Hiah Rst : 0 : En Lck

## RANGE (Control & Display):

J Type :  $0 \sim 600$  Deg. C. K Type :  $0 \sim 1250$  Deg. C. Pt -100 (RTD) :  $0 \sim 400$  Deg. C. Hysterisis :  $0 \sim 99$  Deg. C. Prop. Band. :  $0 \sim 99$  Deg. C. Cycle Time: :  $0 \sim 99$  Seconds. Manual Reset:  $0 \sim 99$  Deg. C. \* For J & K Type Thermocouple ,

Instrument can display/Control only 10 Degrees Below Ambient Temperature.

## **SPECIFICATIONS:**

INPUTS: J, K & Pt-100

OUTPUT: 1 NO/NC relay, 5A/230V

Aux. Supply: 230V,50Hz.

Control Logic: Heat/Cool (On/Off only)

Resolution: 1 Deg.

Bezel Size: 96mm \* 96mm

Depth: 90mm

Cutout: 92mm \* 92mm.