

## ALCT 66A

## Smart Leakage Clamp Meter

- Compact size leakage clamp meter
- Current measurement from 1µA to 60A
  Large jaw opening
- Data storage facility upto 99 records
- · Complies with CE, CAT protection
- · Software facility for reports



Agam ALCT 66 A is a high-accuracy high sensitivity leakage current clamp meter, specially designed for testing AC leakage current. It has the latest CT technology and digital integration technology, with small-size, high precision and perfect function. It is suitable for applications in Utilities, Communication industry, Railways, Oil fields, Building wiring segment, Processing industries, etc. Its sensing core is made of special alloy, using magnetic shielding technology, which lets it almost unaffected by the external magnetic field and ensures high accuracy, high stability and high reliability of constant measurement

| Specifications            | Range                  |                         | Accuracy  |
|---------------------------|------------------------|-------------------------|-----------|
| Leakage<br>Current<br>(A) | Range                  | 0.001mA<br>to<br>60.00A | ±(1.5%+5) |
|                           | Voltage<br>(frequency) | 0V~600V<br>(50Hz/60Hz)  | V         |
|                           | Resolution             |                         | 1uA       |

| Display Mode  | 4 Digits LCD Display  |  |
|---|---|--|
| Auto Range  | √ Jigito EGD Display  |  |
|   | ·   |  |
| Jaw Capacity  | 25mm×30mm   |  |
| RS-232  | √   |  |
| Data Storage  | 99  |  |
| Peak Value  | V   |  |
| Data Hold   | V   |  |
| Auto Power Off  | 5 Minutes   |  |
| Low Battery Indication  | ≤7.2V   |  |
| Over-Range Display  | OL  |  |
| Test Mode   | Clamp CT, Integral Approach   |  |
| Environmental Specs   | Operating Temperature: -10 to 40 °C Storage Temperature: -20 to 60° C Relative humidity: 80% @ -10 °C to 40 °C Below 70% @ -20 °C to 60°C |  |
| Applicable Safety Standards: Pollution grade 2, IEC 61010-1, IEC 61010-2-032, CAT II 600V |   |  |
| General Characteristics   |   |  |
| Power   | 9V Battery (6F22)   |  |
| LCD Size  | 32mm X 15mm   |  |
| Product Net Weight  | 120g  |  |
| Product Size  | 175mm X 70mm X 38mm   |  |
| Standard Accessories  | Battery, RS232 Interface Cable, Software CD, Carrying bag   |  |

Marketed by: