

testo 755

Current / Voltage Meter, 200 A AC, 600 / 1000 V AC/DC, Continuity, and Phase Rotation Tester*



Meter automatically detects testing in-process and selects correct meter configuration which saves time and optimizes accuracy

Polarity detection for DC circuits

3-phase sequence check with motor rotation indication

Single lead voltage test with audible indication

Interchangeable measuring tips

Built-in flashlight illuminates your measurements

APO (Automatic Power Off) below 6 VAC

The testo 755 current/voltage testers are fast and easy to use, especially when you are testing many circuits. The convenient open-jaw current tester automatically turns on when voltage exceeds 6V. It then auto-selects the correct parameters and range for your test. These rugged testers are suitable for virtually all your daily electrical measuring tasks. The instruments include important functions such as current, voltage, resistance & continuity. The integrated flashlight enables users to work in poorly lit areas.

The overall design is for convenient testing including interchangeable measuring tips which can be easily updated and maintained. A convenient lead holder is integrated into the housing for safe and easy storage. The testo 755-2 includes important additional features: phase rotation, voltage range up to 1000V, and the unique feature which allows the user to check for voltage using only a single lead.


Testo's history of efficiency, innovation, and quality now extends into the entire electrical lineup. Once again, Testo brings high value, feature-packed products to the HVAC contractor market.

* included on:
testo 755-2

Technical data/accessories

testo 755-1


Current / Voltage meter 200 A AC, 600 V AC/DC, with built-in flashlight includes batteries and measuring tips



Order no. 0590 7551

testo 755-2

Current / Voltage meter 200 A AC, 1000 V AC/DC, with built-in flashlight, continuity, phase rotation, and single probe voltage testing includes batteries and measuring tips



Order no. 0590 7552

Technical Data	testo 755-1	testo 755-2
Voltage measuring range	6 to 600 V AC/DC	6 to 1,000 V AC/DC
Current measuring range	0.1 to 200A AC	
Resistance measuring range	30Ω to 100kΩ	
Continuity testing	< 30 Ω	
Rotating magnetic field testing	-	>100 to 690 V
Single pole phase testing	-	100 to 690 V AC at 50/60 Hz
Display (counts)	4,000	
Measuring point illumination	✓	
Safety category	CAT IV 600 V CAT III 1000 V	
Protection Class	IP 64	
Operating temperature	14 to 122°F (-10 to +50 °C)	
Storage temperature	5 to 140°F (-15 to +60 °C)	
Dimensions	7.3 x 2.4 x 1.6 in. (199 x 62 x 40 mm)	
Weight	0.67 lbs (306 g)	
Warranty	2 years	
Authorizations	TÜV, CSA, CE	
Standards	EN 61243-3:2010, EN 61010-1	
Batteries	2 x AAA	

d.p.v1

Subject to change, including technical modifications, without notice.

Accessories

	Order no.
testo 755 / testo 770 carrying case	0590 0017
Set of replacement measuring tips	0590 0015
Set of safety alligator clips	0590 0008
Set of alligator clips	0590 0009

